

- (1) FINISH GRADE
- (2) JUMBO VALVE BOX & COVER
- 3 CONTROL WIRES WITH 12" MIN.
 SERVICE COIL AND WATERPROOF
 WIRE SPLICE CONNECTORS WIRE
 COLORS PER SPECIFICATIONS
- (4) FLOW SENSOR PER SPECIFICATIONS
- 5) PVC 45 DEGREE ELL (TYP.)
- 6 MINIMUM 10x PIPE DIAMETER UPSTREAM & MINIMUM 5x PIPE DIAMETER DOWNSTREAM OF STRAIGHT PIPE
- 7 PVC 45 DEGREE ELL (TYP.) BUSH DOWN TO FLOW METER SIZE AS NECESSARY

- 8 PVC MAINLINE LENGTH AS REQUIRED - SEE SPECIFICATIONS FOR TYPE AND DEPTH
- 9 GRAVEL (1 CU. FT.)
- (10) CONTINUOUS BRICK SUPPORTS
- (11) VALVE BOX EXTENSIONS AS REQUIRED

NOTES:

SEE PLANS, LEGEND AND SPECIFICATIONS FOR ADDITIONAL INSTALLATION NOTES.

FLOW SENSOR DATA INDUSTRIAL IR SERIES

SECTION/ELEVATION

NOT TO SCALE