



- (1) FINISH GRADE
- (2) JUMBO VALVE BOX & COVER
- (3) CONTROL WIRES WITH 12" MIN. SERVICE COIL AND WATERPROOF WIRE SPLICE CONNECTORS – WIRE COLORS PER SPECIFICATIONS
- (4) FLOW SENSOR PER SPECIFICATIONS
- (5) PVC 45 DEGREE ELL (TYP.)
- (6) MINIMUM 10x PIPE DIAMETER UPSTREAM & MINIMUM 5x PIPE DIAMETER DOWNSTREAM OF STRAIGHT PIPE
- (7) PVC 45 DEGREE ELL (TYP.) BUSH DOWN TO FLOW METER SIZE AS NECESSARY

- (8) PVC MAINLINE – LENGTH AS REQUIRED – SEE SPECIFICATIONS FOR TYPE AND DEPTH
- (9) GRAVEL (1 CU. FT.)
- (10) CONTINUOUS BRICK SUPPORTS
- (11) VALVE BOX EXTENSIONS AS REQUIRED

- (12) PVC MALE ADAPTER (TYP.)
- (13) TORO REMOTE CONTROL ELECTRIC GLOBE VALVE WITH FLOW CONTROL MODEL NO. P220-27-XX (SEE SPECS.)

NOTES:
SEE PLANS, LEGEND AND SPECIFICATIONS FOR ADDITIONAL INSTALLATION NOTES.

SECTION/ELEVATION

(ELECTRIC, PRESSURE REGULATED)
FLOW SENSOR / MASTER VALVE
DATA INDUSTRIAL IR SERIES / TORO P-220 SERIES

NOT TO SCALE